

HT series - Blocked fiberglass sleeving

HT is a braided fibreglass sleeving treated at a high temperature to mould, dye colour then impregnated with silicon. It is widely used as mechanical protection for cables in the electrical motor's market.

Thermal properties:

Thermal class: C
Working temp. -30°C +250°C
Random peaks +320°C

Packaging:

From 0,5 mm. up to 4 mm.
200 meters rolls

from 5 mm. up to 20 mm.
100 meters rolls

Colour:

Black is the standard colour.
Other colours on request.

Size:

Inside Diameter	Tolerance mm	Wall thickness
0,5	+ 0,3 - 0	0,35 ±0,10
1	+ 0,3 - 0	0,35 ±0,10
1,5	+ 0,3 - 0	0,35 ±0,10
2	+ 0,3 - 0	0,35 ±0,10
2,5	+ 0,3 - 0	0,35 ±0,10
3	+ 0,3 - 0	0,40 ±0,10
3,5	+ 0,3 - 0	0,40 ±0,10
4	+ 0,3 - 0	0,40 ±0,10
5	+ 0,3 - 0	0,50 ±0,10
6	+ 0,3 - 0	0,50 ±0,10
7	+ 0,3 - 0	0,50 ±0,10
8	+ 0,3 - 0	0,50 ±0,10
9	+ 0,5 - 0.1	0,60 ±0,15
10	+ 0,5 - 0.1	0,60 ±0,15
12	+ 0,5 - 0.1	0,60 ±0,15
14	+ 0,5 - 0.1	0,70 ±0,15
16	+ 0,5 - 0.1	0,70 ±0,15
18	+ 1.0 - 0.5	0,80 ±0,15
20	+1.0 - 0.5	0,80 ±0,15

Breakdown Voltage:

- HT: 1000 Volt

Applications:

- Motor and transformers connections
- Cable protection
- General electrical usage

Main property:

Property	Results
After heating	No cracking or detachment of the resin. It maintains its flexibility after treatment at 360°C.
Self-extinguishment	Self-extinguishing material. Vertical Test UL1441 VW-1

The values given above are believed to be accurate and given as a matter of information only. As usage conditions are beyond our control we suggest the customer to confirm values and product compatibility prior to its use. We don't guarantee nor accept any responsibility for any particular usage.

Certifications:

UL:  File E311983





UL Online Certifications Directory

UZIQ2.E311983 Sleeving, Flame Retardant - Component

Sleeving, Flame Retardant - Component

ISOLCAVI SAS DI GHIDONI ANNA & C
VIA ABITAZIONE 5/1
40050 MONTEVEGLIO, BO ITALY

E311983

Silicone varnished fiberglass sleeving, Cat. Nos. GVES 1500, GVES-2500, GVES 4000 A, GVES 1500 A, GVES 2500 A, GVES 4000, GVES 7000, HT All Colors.

Marking: Company name, catalog designation and "VW-1" on the outside of the spool and on a separate tag on each end of the sleeving, or on the bundling wrapper or on the outside of the container.

[Last Updated](#) on 2007-03-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories Inc.®"



MATERIAL SAFETY DATA SHEET

1 PRODUCT AND COMPANY IDENTIFICATION

Product identification	HT
Company Identification	Isolcavi sas di Ghidoni Anna Via Abitazione, 5/1 – 40050 Monteveglio (BO) Italy Tel. +39 051 83.24.85 Fax +39 051 83.26.01

2 COMPOSITION / INFORMATION ON INGREDIENTS

Product description: Impregnated or coated insulating fiberglass sleeving, made of glass fibre
Identification of components:
- Glass Fibre
- Impregnating or coating varnish or resin
Components contributing to the hazard: No hazardous components.

3 HAZARD IDENTIFICATION

The product poses, as it is, no known hazard to human health or to the environment.
See n. 5 for hazards in case of fire.

4 FIRST AID

In case of contact with skin: in case of reaction in sensitive individuals, wash with water for several minutes.
In case of contact with eyes: in case of reaction in sensitive individuals, wash with water for several minutes.
If swallowed: seek medical advice.
If inhaled: not specifically concerned.

5 FIRE FIGHTING MEASURES

Extinguishing media: powder/Carbon dioxide (CO₂)/Foam/Water fog
Extinguishing media not to be used: none
Auto flammability of components: over 400°C or not applicable
Special risk resulting from the exposure to combustion gases: this material may release fumes or more or less toxic gases in the event of fire. Exposure to these gases of fumes may pose health risk.
Special protective equipment for fire-fighting personnel: wear self-contained breathing apparatus.

6 MEASURES IN CASE OF ACCIDENTAL LOSS

Individual protective equipment: no special measures required.
Environmental precautions: no special measures required.
Clean-up/absorption method: no special measures required.

7 HANDLING AND STORAGE

Handling: no special measures required.
Storage: preferably store far from fire and inclement weather.

8 EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure limit for humans: none, in normal working conditions.
Special measures for reducing exposure: none in normal working conditions.
Personal protection: do not eat, drink or smoke. Wash hands after handling the material. Keep away from food and beverages. Avoid contact with eyes.

9 PHYSICAL AND CHEMICAL PROPERTIES

Form: solid Color: several pH value: not concerned Initial boiling point: not applicable Flash point: not applicable	Explosivity hazard: not explosive Explosivity limits: not applicable Vapour pressure: not applicable Density: not applicable Solubility: not applicable
--	---

10 STABILITY AND REACTIVITY

Conditions to avoid: no decomposition if used as prescribed. Materials to avoid: no known during normal working conditions. Hazardous decomposition products: none during normal working conditions.
--

11 TOXICOLOGICAL INFORMATIONS

Acute toxicity: not concerned. Local effects: in certain sensitive individuals, may cause slight and brief irritation of the skin and ocular mucous membranes. Sensitization: not concerned.
--

12 ECOLOGICAL INFORMATIONS

Non-biodegradable material. Non-toxic in water. Action on the ozone layer: not available

13 DISPOSAL CONSIDERATIONS

Partially recyclable. Product disposal information: comply with local regulations. Packaging disposal information: comply with local regulations.

14 TRANSPORT INFORMATIONS

Transport is not restricted.

15 REGULATORY INFORMATIONS

This material is not classified as hazardous for the user; respect general rules regarding safe and health.

16 OTHER INFORMATIONS

The product must be used and/or installed by qualified and trained personnel. This MSDS completes the technical data sheets but does not supersede them. The information given herein is based on extent of our knowledge of the product on the publishing date. The information given herein is offered in good faith as accurate. Moreover, users should be aware of the possible hazard incurred when a product is used for any purpose other than its intended use. In no way it relieve the user from knowing and applying all texts governing his/her activity. It is the user's sole responsibility to take the necessary precautions associated with the use of the product. All of the regulatory provisions mentioned are provided to assist the end-user in fulfilling his/her obligations when using a danger product. This list must not be considered as exhaustive. It does not stop the user from making sure that he/she complies with the written obligations other than those previously cited and which rule the fact of keeping and using the product for which hs/she is the sole responsible person.
